

NANO-CERAMIC®



WWW.NANO-CERAMIC.COM INDUSTRIAL PROTECTIVE COATINGS



Transport

What is NANO-CERAMIC Thin Film Coating?

NANO-CERAMIC Thin Film Coating is a revolutionary, ultra-durable, ceramic clear-coating that provides superior scratchresistance and semi-permanent protection for all vehicle finishes, paints and exterior surfaces.



What makes NANO-CERAMIC Thin Film Coating so different?

NANO-CERAMIC Thin Film Coating is more than 4 times stronger than factory paint finishes and can absorb damage that would otherwise affect the appearance and integrity of your paint. This extremely durable ceramic coating reduces swirl marks and light scratches while protecting and preserving factory paint.



Conventional paints like acrylic urethane are simply not strong enough.


NANO-CERAMIC Thin Film Coating is completely resistant to acidic environmental substances like bird droppings, bug residue, acid rain, and tree sap, unlike your vehicle's factory paint, which can be permanently etched and damaged by these substances.

NANO-CERAMIC Thin Film Coating provides advanced protective barriers to your vehicle's surfaces, maintaining both high-gloss and matte finishes.


What are the benefits of applying NANO-CERAMIC Thin Film Coating?

NANO-CERAMIC Thin Film Coating provides vehicles with a superior, near-permanent, clear coating that is resistant to chemical etching, harder than factory paint finishes, and able to greatly reduce swirl marks and fine scratches while leaving a superior, hydrophobic surface that is easier to clean and stays cleaner longer.


Clearcoat, Glass vehicle materials can be treated with one of our NANO-CERAMIC Thin Film CERAMIC Restore the color and shine to plastic trim with advanced hydrophobic and UV protection. Even chrome, aluminum, and other metals can have added protection, as our coatings can withstand temperatures of over 1500°F



Step 1 The surface layer of factory clear coat is damaged and contaminated.



Step 2 Decontamination and polishing the clear coat to produce a smooth and even surface.



Step 3 Restoration of coating thickness with a super-durable layer of NANO-CERAMIC Thin Film





VIDEO
PRODUCT
SCAN
QR CODE



SIO3 GLOSS

Body & Windshield Protection for clearcoat / glass / chrome



Product ID : SIO31A00-32oz 8 Micron SIO21A00-32oz 2 Micron
Consumption : +/- 0.007oz/ft²
Reachable area : +/- 5.000ft² Body + 5.000ft² Windshield
Used for : Clearcoat, windshield, acrylic, glass, chrome
Application field : Transport

How to use: Page 12


Your Fleet will stand out! These Kit-Sets contain all to make trucks and busses protected with a High-Tech ceramic layer.

- Two simple steps: Clean with our Steril Cleaner and Apply
- The original surface is protected against corrosion.
- Makes the surface anti scratch, much easier and quicker to clean, and the adhesion of dirt is reduced drastically.
- Promotes more hygienic surfaces.

This coating has an outstanding hydrophobic effect, and the surface stays cleaner longer. Cleaning intervals as well as the formation of water spots will be greatly reduced.

- Easy to apply**
- Cut cleaning costs**
- Anti-water spot
Anti-corrosion**
- Super hydrophobic**
- Self-cleaning stays cleaner longer**
- Anti-scratch**
- Visibility safety**
- Protects your investment**

Applicator:



Expected Life Duration up to 5 Years+ (2 Years on Glass)



VIDEO
PRODUCT
SCAN
QR CODE



SIO5 MATTE

Body & Windshield Protection for clearcoat / glass / chrome



Product ID : SIO51A00-32oz 2.5 Micron SIO21A00-32oz 2 Micron
Consumption : +/- 0.007oz/ft²
Reachable area : +/- 5.000ft² Body + 5.000ft² Windshield
Used for : Clearcoat, windshield, acrylic, glass, chrome
Application field : Transport

How to use: Page 12


Your Fleet will stand out! These Kit-Sets contain all to make trucks and busses protected with a High-Tech ceramic layer.

- Two simple steps: Clean with our Steril Cleaner and Apply
- The original surface is protected against corrosion.
- Makes the surface anti scratch, much easier and quicker to clean, and the adhesion of dirt is reduced drastically.
- Promotes more hygienic surfaces.

This coating has an outstanding hydrophobic effect, and the surface stays cleaner longer. Cleaning intervals as well as the formation of water spots will be greatly reduced.

- Easy to apply**
- Cut cleaning costs**
- Anti-water spot
Anti-corrosion**
- Super hydrophobic**
- Self-cleaning stays cleaner longer**
- Anti-scratch**
- Visibility safety**
- Protects your investment**

Applicator:



Expected Life Duration up to 5 Years+ (2 Years on Glass)



APPLY
MOVIE SCAN
OR CODE



APPLY
MOVIE SCAN
OR CODE

CLEAN

Steril Cleaner hard surface pretreatment



Product ID : CLEAN0500 16oz / CLEAN5000 1.32gal
CLEAN020L 5gal
Consumption : +/- 0.01oz/ft²
Used for : Glass, ceramics, mirrors, marble wood steel
Application field : Automotive

100% Steril with nano interlock technology (active lifting encapsulate the grease from the surface)

- Surface cleaning and residue removal.
- Cleaning gloves, notebooks, phones or any other item entering the cleanroom.
- Wipe down for pass-through to controlled environments.
- Pretreatment for the application of thin film coating

- Easy to apply spray & wipe**
- Indoor Outdoor**
- Remove grease**
- 100% Steril**
- Visibility Safety**

Applicator:



100% Steril

SIRP

Repellent Protector windshield / mirrors



Product ID : SIRP0500 16oz
SIRP5000 1.32gal / SIRP020L 5gal
Consumption : +/- 0.007oz/ft²
Used for : Glass, acrylic, chrome, vinyl
Application field : Automotive

SIRP is an ultra long-lasting invisible surface coating which forms semi-permanent molecular bonds with the surface. The main function of treating hard surfaces with SIRP is to seal tiny pores, making it a smoother surface that will repel water and contaminants. This product is indispensable for bathrooms

- Two simple steps: Clean with our Steril Cleaner and Apply
- Makes the surface much easier and quicker to clean, and the adhesion of dirt is reduced drastically.
- Promotes more hygienic surfaces
- This coating has an outstanding hydrophobic effect, and the surface stays cleaner longer. Cleaning intervals as well as the formation of water spots will be greatly reduced.


Expected Life Duration up to 12 washes

How to use: Page 15

- Easy to apply**
- Indoor Outdoor**
- Cut cleaning costs**
- Anti-water spot**
- Super hydrophobic**
- Self-cleaning Stays cleaner longer**
- Visibility Safety**

Applicator:





SHRE

Pure Shine Shampoo all exterior surfaces

Product ID : SHRE1000 32oz
SHRE5000 1.32gal / SHRE020L 5gal

Consumption : 0.7oz : 2.5gal Water

Used for : Daily cleaning

Application field : Automotive



Reactivating Pure Shine Shampoo is an advanced technology, multi-purpose foaming cleaner containing a rinsing aid that will leave hard surfaces nearly dry after rinsing with clean water.

To assure the "easy-to-clean" effect that our nano layers provide, surfaces should be free of dyes, waxes or polymer sealants.

This multi-purpose cleaner contains no polymers or colors and will not leave a film of chemicals behind on the surface.

100% Safe to use for cleaning all non-porous surfaces and meets food grade classification for kitchens.

Contains no colouring chemicals which can discolor surfaces.

Dilution ratio 1: 500 (super economical)

- Easy to apply**
- Easy to clean**
- Stays cleaner longer**
- Food grade**

Applicator:



MPCL

Multi Purpose Cleaner all interior surfaces

Product ID : MPCL0500 16oz
MPCL5000 1.32 / MPCL020L 5gal

Consumption : 0.017oz/ft²

Used for : Cleaning all interior surfaces

Application field : Automotive



The All-Purpose Cleaner is a fast, all-surface interior cleaner, low foaming, odor free, and especially suitable for removing stubborn stains from carpets, fabrics, vinyl, plastics and leather safely.

- It is very easy to clean dirt.
- Ready-to-use mixture with the right chemical strength and safe to use
- Of course it is safe for the surface of fabrics, carpets, plastics, leather, rubber and does not fade paint.
- Quickly remove dirt, dust and food scraps

Safe to use does not harm the surface

- Easy to apply spray & wipe**
- No discoloration**
- Indoor Outdoor**
- Quick to use**
- Spills are easy to remove**
- Cleaner for longer**



APPLY
MOVIE SCAN
QR CODE

STEP

One Step Polish

High gloss / zero swirl

- Product ID** : STEP0250 8.5oz
- Consumption** : 0.017oz/ft²
- Used for** : Clearcoat, gelcoat, glass and acrylic
- Application field** : Automotive



Only this High Quality Polish Compound together with the recommended pads assure that every yacht can be polished from deep scratches till high gloss/zero swirl in one single step.

This saves an enormous amount on working hours as polishing takes normally 65% of the total process to make a yacht a thin film nano layer.

Purple Wool Heavy Cutting Pad cuts like natural sheepskin but finishes like a polish pad. Aggressively removes P1500 grit scratches, leaving a lustrous finish with no hazing by reducing compounding swirls.


The Cutting Pad is constructed with a blue foam and white microfiber. The Micro Cutting Pad with orange foam and white microfiber, the Polishing Pad is constructed with a black foam and black microfiber.

The pad serie is available 5.5 inch and 3 inch.

- Cut polish costs**
- Zero swirl and hologram**



Thin Film Protection Plan for Trucks and Buses



HOW TO USE:

NANO-CERAMIC SIRP-SIO3-SIO5 Thin film coatings

These products can be stored for up to 24 months (*in a dry, temperature-stable, dark environment*)

Ambient temperature:

41-86°F Avoid direct sunlight and/or high air humidity.

CLEANING

Clean the surface thoroughly with our Steril Cleaner until it is absolutely clean. If necessary, use our Scrub Cleaner or Reactivating Pure Shine Shampoo in advance. Make sure that all contamination is removed so that the glass coating can bind properly onto a clean surface. Make sure that the surface is completely dry before application!

APPLICATION OF SIRP

Spray a layer of nano SIRP on the surface and rub it in with a dry microtowel, keep rubbing it into the surface with strong pressure and wipe until all the product is even and scrubbed and only a little hazing / residue is visible **gently** wipe off this hazing / residue with a clean microfiber cloth after about a minute There is only a little pressure needed to remove the hazing completely. Curing time 1 hour.

APPLICATION OF SIO3-SIO5

Our coatings have best results on new on almost like new surfaces, we recommend to polish the surface if needed. Wear nitril gloves to clean the surface with our Steril Pretreatment Cleaner. (without wearing gloves, the oil from your hands may appear via the towel onto the surface) !!

Use more than one clean cloth to remove the dirt from the surface. (Please make sure you don't brush the dirt around on the surface by using dirty clothes.) Making the clearcoat-chrome-glass-surface clean is the most important issue. If the surface is not super steril than you will experience chemical reactions between our coatings and the still available contamination what is then visible into the ceramic layer when it is cured. In that case you will need to polish the surface again. So please don't hurry in carrying out this preparation work, but instead focus on this for 100%.

Learn the right application technique > Watch and Study the Apply Video scanning the QR Code on this page or on the packaging

(fragment **BASE COAT**) OPTIONAL

Use nitril gloves! Remove the plastic inner closure from the bottle and put in the dripper. Shake bottle before use! We recommend to apply the surface in easy to handle segments of about 15"x 15"inch, following the panels shape and corner lines and use these lines for overlaps. Put 8-10 drops BASE COAT on the suede mini towel using the applicator block underneath, devide the coating properly by going 3 times over the same surface, wait till it lights up (+/- 25sec) and remove the residue carefully, and buff it lightly use a separate micro towel for this. Wait 2 hours before you continue with the application of one of our hydrophobic Top Coatings. After 2 hours BASE COAT is 80% cured and ready to receive one of our TOP COATINGS. After about 7 days the BASE COATING has been fully cured and is almost unremovable.

(fragment TOP COAT **SIO3-SIO5**)

Use nitril gloves! Remove the plastic inner closure from the bottle and put in the dripper. Shake t

he bottle before use! We recommend to apply the surface in easy to handle segments following the panel shape and corner lines and use these lines for overlaps.

Put 6-8 drops 40x40cm (15"x 15"inch), (if start use more drops as the towel is otherwise too dry) TOP COATING on the suede mini towel using the applicator block underneath. Start dividing it from out of the middle of the surface and keep spreading it around by light pressure in criss-cross motions until the product is evenly distributed.

MOST IMPORTANT keep on doing this till no product residue is visible anymore. If you use too much coating and/or spreading it out from example one start position in a corner of a panel then you will not be able to divide it properly towards the other side and it will roll-up on each other and form a not equal layer. To use too much coating and not divide it equally is the second most critical point !!

When you apply TOP COATING in this correct way, then there is no need to use a micro towel for polishing anymore.

(fragment **SIO2 SAFETY VISION**)

Apply the nano layer SAFETY VISION COATING with the cotton apply pad. Spread 10-15 drops 50x60cm (20"x 25"inch) of SAFETY VISION COATING on the cotton pad and apply rubb it in motions on the windshield with firm pressure until all of the product is evenly distributed and only very little residue is visible.

Remove the coating residue with a soft clean microfiber cloth after about a minute and buff the glass/panels gently to take the veils away. There is not much pressure necessary to remove it completely. Note: dry the dripper and close the bottles tightly if you want to save the content for future use. At normal ambient temperature the Nano layers are sufficiently cured after approximately 6 hours (or 2 hours Infrared) (avoid water contact during this time).

Application Video SGS Cert.



What is NANO-CERAMIC Permanent Coating?

NANO-CERAMIC permanent coating is the latest generation of protective coating which transforms paint into a hard ceramic, providing superior scratch resistance and permanent protection for all exterior or interior surfaces.


NANO-CERAMIC permanent coating is 600°F resistant and more than 6 times stronger than traditional acrylic based paint finishes, and is effectively preventing damage that would otherwise affect the appearance and integrity of the original surface.

Zero Maintenance for 3 decades to come!

Our NANO-CERAMIC permanent coating is rigorously tested by an independent testing laboratory according to the European standard for outdoor paints (EN 1504-2) please find the test report on page 19.

Can NANO-CERAMIC Permanent Coating be applied on any surface?


The NANO-CERAMIC permanent coating can be applied directly or indirectly on all kinds of interior and /or exterior surfaces (absorbing and non-absorbing), such as concrete, steel, wood, acrylic, gypsum and many more.



Is NANO-CERAMIC Permanent Coating self-cleaning?

NANO-CERAMIC permanent coating provides a permanent hydrophobic surface that is self cleaning, easier to clean and stays cleaner longer as water and dirt can not penetrate the ceramic layer. NANO-CERAMIC permanent coating is resistant to water vapor and water absorption.

Cross Section of Coating System



Conventional paints

Conventional gelcoats are a mixture with Epoxy or polyester resins, of which the quality of resin and pigments are the most important factor in the ultimate strength.

Most have a lifespan of 15 years, with hardness and color retention (sun fading) being the most common problems in keeping the desired object at an aesthetically pleasing level.

There is no better option than protecting your fleet with a NANO-CERAMIC Thin Film or Permanent Coating!

Do not wait till the surface get worse, most easy is to apply wipe or spray when the surfaces are still in new or in nearly new condition and the cost do not outweigh the benefits



SI11

2-Component (2K)

Topcoat Transparent

for glossy surfaces

Product ID	: SI112000 67oz / 4.2 lbs
Consumption	: 3 layers 0.06lbs/ft ² - 0.96oz/ ft ² = 3 mil/ 70ft ²
Reachable area	: 2 layers 0.04lbs/ft ² - 0.64oz/ ft ² = 2 mil/140ft ² : 1 layer 0.02lbs/ft ² - 0.32oz/ ft ² = 1 mil/210ft ²
Hardness	: H9
Used for	: Fiberglass, steel, aluminium, plastics, wood
Application field	: Transport

SI11 is an incredibly strong 2-component paint system which forms a durable matrix of molecular bonds (transformation to ceramic) resulting in permanent protection of the surface.

Three simple steps: Clean, Dry, and Apply.

- Easily repels water, dirt, dust, and pollutants.
- This coating is permanent hydrophobic.
- Restores damaged finishes and reduces cleaning intervals.
- Resistant to all kinds of chemicals and UV radiation.
- Superior anti-pollution and anti-corrosion properties.
- This coating can withstand temperatures of 300°C.

Expected Life Duration up to 30 years+



How to use: Page 20

- Easy to apply
- Cut cleaning costs
- Anti-water spot
Anti-corrosion
- Permanent hydrophobic
- Self-cleaning stays cleaner longer
- Anti-scratch
- Save on fuel
Save on repaints
- Protects your investment



SI21

2-Component (2K)

Paint Strongest White

for glossy surfaces

Product ID	: SI212000 67oz / 5.3 lbs
Consumption	: 3 layers 0.044lbs/ft ² - 0.56oz/ ft ² = 3 mil/120ft ²
Reachable area	: 2 layers 0.030lbs/ft ² - 0.37oz/ ft ² = 2 mil/160ft ² : 1 layer 0.014lbs/ft ² - 0.19oz/ ft ² = 1 mil/240ft ²
Hardness	: H8
Used on	: Gelcoat, fiberglass, steel, aluminium, plastics, wood
Application field	: Transport

SI21 is an incredibly strong 2-component paint system which forms a durable matrix of molecular bonds (transformation to ceramic) resulting in permanent protection of the surface.

Three simple steps: Clean, Dry, and Apply.


- Easily repels water, dirt, dust, and pollutants.
- This coating does not absorb any water
- Resistant to all kinds of chemicals and UV radiation.
- This coating can withstand temperatures of 300°C

Expected Life Duration up to 25 year+



How to use: Page 20

- Easy to apply
Repaintable
- Cut maintenance costs
- Anti-water spot
Anti-corrosion
- Permanent hydrophobic
- Self-cleaning stays cleaner longer
- Anti-scratch
- Visibility
- Protects your investment



SI32

2-Component (2K)

Undercoat-Bedliner Textured Transparent for semi gloss surfaces

Product ID	: SI322000 67oz / 4.4 lbs
Consumption	: 3 layers 0.050lbs/ft ² - 0.76oz/ ft ² = 3 mil/ 90ft ²
Reachable area	: 2 layers 0.033lbs/ft ² - 0.51oz/ ft ² = 2 mil/180ft ² : 1 layer 0.017lbs/ft ² - 0.25oz/ ft ² = 1 mil/270ft ²
Hardness	: H9
Used for	: Fiberglass, steel, aluminum, plastics, an many more
Application field	: Transport

SI32 is an incredibly strong 2-component paint system which forms a durable matrix of molecular bonds (transformation to ceramic) resulting in permanent protection of the surface.

Three simple steps: Clean, Dry, and Apply.


- Easily repels water, dirt, dust, and pollutants.
- This coating is permanent hydrophobic.
- Restores damaged finishes and reduces cleaning intervals.
- Resistant to all kinds of chemicals and UV radiation.
- Superior anti-pollution and anti-corrosion properties.
- This coating can withstand temperatures of 300°C.

Expected Life Duration up to 30 years+



How to use: Page 20

-  **Impact Resistance**
2lbs/2.5ft
-  **Easy to apply**
-  **Cut cleaning costs**
-  **Anti-water spot**
Anti-corrosion
-  **Permanent hydrophobic**
-  **Self-cleaning**
stays cleaner longer
-  **Anti-scratch**
-  **Save on fuel**
Save on repaints
-  **Protects your investment**



SI33

2-Component (2K)

Undercoat-Bedliner Textured Black for semi gloss surfaces

Product ID	: SI332000 67oz / 4.4 lbs
Consumption	: 3 layers 0.050lbs/ft ² - 0.76oz/ ft ² = 3 mil/ 90ft ²
Reachable area	: 2 layers 0.033lbs/ft ² - 0.51oz/ ft ² = 2 mil/180ft ² : 1 layer 0.017lbs/ft ² - 0.25oz/ ft ² = 1 mil/270ft ²
Hardness	: H9
Used for	: Fiberglass, steel, aluminum, plastics, an many more
Application field	: Transport

SI33 is an incredibly strong 2-component paint system which forms a durable matrix of molecular bonds (transformation to ceramic) resulting in permanent protection of the surface.

Three simple steps: Clean, Dry, and Apply.

- Easily repels water, dirt, dust, and pollutants.
- This coating does not absorb any water
- Resistant to all kinds of chemicals and UV radiation.
- This coating can withstand temperatures of 300°C

Expected Life Duration up to 25 year+



How to use: Page 20

-  **Impact Resistance**
2lbs/2.5ft
-  **Easy to apply**
Repaintable
-  **Cut maintenance costs**
-  **Anti-water spot**
Anti-corrosion
-  **Permanent hydrophobic**
-  **Self-cleaning**
stays cleaner longer
-  **Anti-scratch**
-  **Visibility**
-  **Protects your investment**

How to use our Permanent Coating System:

These products can be stored for up to 24 months (in a dry, temperature-stable dark environment)


Processing Temperature:

Ambient temperature: 41-86°F
Avoid direct sunlight, Rain and /or high humidity.

IMPORTANT:

Before you use a NANO-CERAMIC product, please make sure you wear suitable protection gear. We always recommend using a paint suit, respirator mask and latex or nitrile gloves.

Outfit/Applicators:



Application information

The SI11/SI21/SI31/SI33 coatings can be applied directly or indirectly on all surfaces (porous and non-porous) such as concrete, steel, wood, acrylic, gypsum, painted or unpainted surfaces, indoors, or outdoors. The surface underneath will be superbly protected against erosion and corrosion and will stay cleaner longer. Cleaning becomes quicker, easier, and less expensive, as special cleaning agents are unnecessary.

Preparation

Make sure the surface is free from any contamination and dirt. A zinc rich primer can be used in case of problems with the substrate. **Warning the surface must be completely dry before application and must stay dry for 6 hours after application after application!**

The 2-Component Permanent Coating System

Mix the can SI11B-SI21B-SI31B-SI33B with the can of SI11A-SI21A-SI31A-SI33A by pouring can B into can A, or measure exactly by net weight in a ratio of 7:3 and mix very well, or measure exactly by net weight in a ratio of 9:1 and mix thoroughly with a power agitator.

Carefully pour the mixed contents into a professional paint sprayer, and spray in thin layers until the surface reaches your desired thickness. Let the surface dry for 24 hours. It is touch-dry in 1 hours, after 4 hours, 85% cured, and the remaining 15% (transformation into ceramics) is fully cured after 7 days.

Be aware that the mixed contents cannot be stored longer than 3 hours.

The surface can simply be maintained with a high pressure washer at 80 bar using our biologically degradable Reactivating Shampoo SHRE.

Tool cleaning

The individual components, as well as the mixing system of the paint sprayer, can be diluted and cleaned using our THIN Thinner Solvent.

SOLV

 Thinner solvent

for all types of our ceramic paint & coating



Article Nr. : SOLV0400 14oz / 0.8 lbs


All our paints and coatings are ready to use, for certain spray applications, especially dark colors who require more than average color pigments, it may be necessary to use a little thinner solvent to achieve optimum flowability.

VIDEO



YouTube

TEST (EN 1504-2)



Color card

Other colors need minimal 100kg

Residential

SI13 White Egg-Shell (Flat Finish) 15/25 (20/60°)	SI41 Textured White Semi Gloss 41/69 (20/60°)
SI15 White Egg Shell (Flat Finish) 18/28 (20/60°)	SI42 Textured White Matte 11/21 (20/60°)
SI21 White Gloss 49/77 (20/60°)	
SI22 White Satin 33/59 (20/60°)	

Wood

SI11 Transparent Gloss 51/78 (20/60°)
SI12 Transparent Matte 11/21 (20/60°)

Industrial

SI11 Transparent Gloss 51/78 (20/60°)
SI21 White Gloss 49/77 (20/60°)
SI22 White Satin 33/59 (20/60°)

Marine

SI12 Transparent Matte 11/21 (20/60°)
SI41 Textured White Semi Gloss 41/69 (20/60°)
SI42 Textured White Matte 11/21 (20/60°)

Military

SI31 Textured Transparent Semi Gloss 41/69 (20/60°)
SI33 Textured Black Semi Gloss 41/69 (20/60°)

Antifouling

SI14 Color 3141 (20/60°)



NANO-CERAMIC®



WWW.NANO-CERAMIC.COM INDUSTRIAL PROTECTIVE COATINGS



The Leader in Durability

Did you know?

That our coatings are made of pure silica sand, which is the most common element on Earth?

Dealer