

NANO-CERAMIC®

WWW.NANO-CERAMIC.COM INDUSTRIAL PROTECTIVE COATINGS



Industrial Objects Permanent Coating System

What is NANO-CERAMIC UVA Topcoat?

NANO-CERAMIC® UVA Topcoat is an innovative low-VOC, non-PFAS, sprayable protective coating designed especially for the demanding conditions of trucks and buses. This self-leveling system forms an ultra-hard, glass-like hydrophobic barrier that delivers superior protection and a sleek, high-gloss finish.

Engineered for extreme durability, UVA Topcoat resists harsh weather, intense UV radiation, road salts, and aggressive chemicals commonly encountered in road transport. It is fully safe and compliant for use on passenger and cargo vehicles—including food-contact areas—ensuring both safety and performance.

Powered by cutting-edge nanotechnology, UVA Topcoat extends the service life of critical surfaces such as polyester, epoxy, polyurethane, acrylic resins, steel, aluminum, composites, and wood. It effectively prevents corrosion, surface degradation, and wear—making it the ideal all-in-one solution to protect exterior and interior surfaces.

Why UVA Topcoat is a Game-Changer in Protection?

For decades, protective coatings like epoxy, polyurethane (PU), and acrylic have been the industry standard. However, they all share a critical weakness—UV degradation. Prolonged exposure to sunlight causes these coatings to yellow, crack, and deteriorate, leading to costly maintenance and premature failures.

Superior Performance at the Lowest Cost.

UVA Topcoat isn't just another coating—it's a next-generation solution designed to simplify and reduce costs maintenance. By replacing complex, multi-layer systems with a single, high-performance layer, it streamlines your coating process.

Applied directly over existing automotive paints and materials, UVA Topcoat eliminates the need for expensive refinishing or additional topcoats, saving both time and money. Its advanced chemistry and ease of application make traditional coating systems obsolete for floors, pipelines, storage tanks, bridges and many more.

Whether protecting these surfaces, UVA Topcoat simplifies your workflow and maximizes value—demonstrating that outstanding durability and protection don't have to come with a premium price.


Where can UVA Topcoat be used?

UVA Topcoat is highly versatile and ideal for a wide range of industrial and factory applications:

- Exterior Structures – Facades, loading bays, storage tanks, and pipelines for long-term weather and UV protection
- Production Areas – Floors, walls, and machinery housings with chemical, abrasion, and impact resistance
- Storage & Logistics Zones – Racks, shelving, conveyor systems, and container exteriors for easy cleaning and durable finish
- Utility Equipment & Framework – Beams, supports, ducts, and enclosures with corrosion resistance against moisture and harsh environments

Compatible with both new installations and maintenance recoats, UVA Topcoat adapts to varied materials and demanding conditions typical in industrial operations.

How it Works



Freedom in Protection Years

Long-Lasting Protection, Layer by Layer

A single 6 μm (micron) layer applied using HVLP spray technology can provide up to 8 years of protection. Need more durability? Just add more layers—it's that simple.

Apply wet-on-wet: once the first coat flashes off (dry to the touch but still tacky), you can immediately apply the next. This method prevents trapped gases and creates a seamless, chemical-resistant film with hydrophobic properties—making surfaces easier to clean and maintain.



Coverage & Application Efficiency

UVA Topcoat is engineered for maximum efficiency with minimal material use—delivering high-performance protection at a fraction of the volume required by traditional coatings.

Recommended usage is approximately $\pm 0.025 \text{ lbs/ft}^2$ per layer (by wipe or spray), resulting in a film thickness of around 6 microns, with one liter covering up to 800 ft^2 .

Color Tinting Option


For customized aesthetics, UVA Topcoat can be tinted using our colorants on pages 22–23. These high-performance, solvent-free pigments deliver long-lasting color stability and excellent UV resistance—ideal for exterior and interiors, areas where both protection and appearance are essential. Perfect for any visible surface requiring a durable, colored finish without compromising the coating's hydrophobic and chemical-resistant properties.



Quality Comparison of paints technologies

In case written in bold font it means existing shortcomings in quality.

Characteristics	Acrylic Latex walls ceilings	Acrylic walls floors	Epoxy floors	Polyurethane waterproofing	UVA Topc all surfaces
Primer	Yes	Yes	Yes	Yes	No
Adhesion Strength	Poor	Poor	Poor	Poor	Excellent
Cross Cut Test	Poor	Poor	Good	Poor	Excellent
Abrasion Resistance	Poor	Poor	Average	Poor	Excellent
UV Radiation Resistance	Average	Average	Poor	Good	Excellent
Artificial Atmospheric Agents	Poor	Poor	Good	Good	Excellent
Colour Retention	Average	Average	Poor	Poor	Excellent
Gloss Retention	Poor	Poor	Poor	Poor	Excellent
Chemical Resistance	Good	Good	Good	Poor	Excellent
Severe Chemical Attack	Poor	Poor	Average	Poor	Excellent
Temperature Resistance	140°F	196°F	350°F	505°F	550°F
Thermal Shock Resistance	Good	Good	Poor	Good	Excellent
Carbon Dioxide Permeability	Poor	Poor	Good	Poor	Excellent
Permeability water vapour	Average	Average	Good	Average	Excellent
Water Absorption Rate	5-15%	1%	2%	3%	0%
Aging at 70°C	Poor	Poor	Good	Average	Excellent
Adhesion Strength Pull-off	Poor	Average	Good	Poor	Excellent
Impact Resistance	Poor	Average	Good	Poor	Excellent
Anti-Graffiti	No	No	No	No	Yes
Anti-Termite (Wood)	No	No	No	No	Yes
Hydrophobic Self Cleaning	No	No	No	No	Yes
Easy to Clean	No	No	No	No	Yes
Total Solar Reflectance (TSR)	60 (white)	60 (white)	60 (white)	60 (white)	88 (white)
Expected Lifetime in Years	<7	<7	<5-15	<5-15	8/16/24





S104

1-Component (2K)

Topcoat Transparent for glossy surfaces



Product ID : S1041LUVA 32 oz / 2.03 lbs S10405UVA 16 oz / 1 lbs
Consumption : 3 layers +/- 0.075 lbs/ft² - 0.12 oz/ft² 18 micron = 200 ft²
Reachable area : 2 layers +/- 0.050 lbs/ft² - 0.08 oz/ft² 12 micron = 400 ft²
: 1 layer +/- 0.025 lbs/ft² - 0.04 oz/ft² 6 micron = 800 ft²

Hardness/Cupping : H9 / Flexibility ISO 1520 >21mm

Used for : Facades, floors, storage tanks, pipelines dll.

Application field : Buildings, factories, offshore structures, bridges, dll.

S104 is an incredibly strong 1-component paint system which forms a durable matrix of molecular bonds (transformation to ceramic) resulting in permanent protection of the surface.

Three simple steps: Clean, Dry, and Apply.

- Easily repels water, dirt, dust, and pollutants.
- This coating is permanent hydrophobic.
- Restores damaged finishes and reduces cleaning intervals.
- Resistant to all kinds of chemicals and UV radiation.
- Superior anti-pollution and anti-corrosion properties.
- This coating can withstand temperatures of 550°F.

Expected life duration 4-16 or 24 Years (layer thickness)



Easy to apply
Repaintable



Cut maintenance costs



Anti-water spot
Anti-corrosion



Permanent hydrophobic



Self-cleaning
Cleaner for longer



Anti-scratch



Impact Resistance
30"-2lbs



Protects your
investment

S124

1-Component (1K)

Topcoat Transparent for matte surfaces



Product ID : SI241LUVA 32 oz / 2.13 lbs SI2405UVA 16 oz / 1.05 lbs
Consumption : 3 layers +/- 0.075 lbs/ft² - 0.12 oz/ft² 18 micron = 200 ft²
Reachable area : 2 layers +/- 0.050 lbs/ft² - 0.08 oz/ft² 12 micron = 400 ft²
: 1 layer +/- 0.025 lbs/ft² - 0.04 oz/ft² 6 micron = 800 ft²

Hardness/Cupping : H9 / Flexibility ISO 1520 >21mm

Used for : Facades, floors, storage tanks, pipelines dll.

Application field : Buildings, factories, offshore structures, bridges, dll.



Easy to apply
Repaintable



Cut maintenance costs



Anti-water spot
Anti-corrosion



Permanent hydrophobic



Self-cleaning
Cleaner for longer



Anti-scratch



Impact Resistance
30"-2lbs



Protects your
investment





Multi-Grade Color Protection – Super Transparent

For boats where weight, speed, and durability matter, our advanced hybrid coating system offers a breakthrough: vibrant transparent tints or metallic finishes without sacrificing performance. By blending NANO-CERAMIC® Super Transparent Colorants into our UVA Topcoat, you get:

Ultra-thin coating (<15 microns) = minimal weight

H9 surface hardness = max scratch resistance

Hydrophobic & anti-fouling = fast cleaning, less drag

UV & salt resistant = marine-grade longevity

Clear or colored: keep visibility through glass or plexi

Optional metallic effect for custom marine finishes



TR.OXIDE YELLOW A-2R 130
Masstone
Tint
77492-1 3.2 oz



YELLOW A-F2G 100
Masstone
Tint
11785 3.2 oz



YELLOW A-H3G 100
Masstone
Tint
11781 3.2 oz



YELLOW A-HRD 100
Masstone
Tint
21108 3.2 oz



ORANGE A-HLD 100
Masstone
Tint
11780 3.2 oz



TRANSOXIDE RED A-G 130
Masstone
Tint
77491-1 3.2 oz



RED A-D3GD 130
Masstone
Tint
56110 3.2 oz



PINK A-E 130
Masstone
Tint
73915 3.2 oz



RED VIOLET A-ER 130
Masstone
Tint
73900 3.2 oz



VIOLET A-RL 100
Masstone
Tint
51319 3.2 oz

Perfect for:

Factory safety paths & door panels

Interior partitions & wall panels

Equipment housings & control panels

Stainless/aluminum rails



YELLOW A-N4G 100-ST
Masstone
Tint
279376 3.2 oz



RED A-P2Y 100-ST
Masstone
Tint
289404 3.2 oz



PINK A-EB 100-ST
Masstone
Tint
287516 3.2 oz



BLUE A-BTR 100-ST
Masstone
Tint
290247 3.2 oz



BLUE A-BG 100
Masstone
Tint
74160 3.2 oz



GREEN A-GNX 130
Masstone
Tint
74260 3.2 oz



BLACK A-N 100
Masstone
Tint
77266 3.2 oz



OXIDE YELLOW A-BV 100
Masstone
Tint
771740 3.2 oz



BLUE A-BTG 100-ST
Masstone
Tint
275536 3.2 oz



GREEN A-GBX 100-ST
Masstone
Tint
323291 3.2 oz



BLACK A-NB 100-ST
Masstone
Tint
289518 3.2 oz



BLACK A-NY 100-ST
Masstone
Tint
272060 3.2 oz



OXIDE YELLOW A-CR 100
Masstone
Tint
77310 3.2 oz



OXIDE YELLOW A-R 100
Masstone
Tint
77492 3.2 oz



OXIDE RED A-B 100
Masstone
Tint
77491 3.2 oz



WHITE A-R 100
Masstone
Tint
77891 3.2 oz

What makes NANO-CERAMIC Permanent Coating System so durable?

NANO-CERAMIC permanent coating system is the latest generation of protective coating which transforms paint into a hard ceramic, providing superior scratch resistance and near-permanent protection for all exterior or interior surfaces.

NANO-CERAMIC permanent coating system is 600°F resistant and more than 4 times stronger than traditional acrylic based paint finishes, and is effectively preventing damage that would otherwise affect the appearance and integrity of the original surface.

Zero Maintenance for decades to come!

Our NANO-CERAMIC permanent coating system is rigorously tested by an independent testing laboratory according to the European standard for outdoor paints (EN 1504-2) as per test report page 19 as here below.

Can NANO-CERAMIC Permanent Coating System be applied on any surface?


The NANO-CERAMIC permanent coating system can be applied directly or indirectly on all kinds of interior and /or exterior surfaces (absorbing and non-absorbing), such as concrete, steel, wood, acrylic, gypsum and many more.



Is NANO-CERAMIC Permanent Coating System self-cleaning?

NANO-CERAMIC permanent coating system provides a permanent hydrophobic surface that is self cleaning, easier to clean and stays cleaner longer as water and dirt can not penetrate the ceramic layer. NANO-CERAMIC permanent coating system is resistant to water vapor and water absorption.


Cross Sections of NC® Coating Systems



Other paints are simply not suitable for longterm harsh outdoor environments.

In order to avoid poorly maintained properties (concrete rot, chipped and weathered paint, etc) for the next decades, our Permanent Coating System is simply the best solution to keep the value of your investment in place.

Superior in Color & Gloss Retention



A special selection of high grade tinting chemicals computerized dispersed in a superior ceramic resin.

Conventional gelcoats are a mixture with Epoxy or Polyurethane resins, of which the quality of resin and pigments are the most important factor in the ultimate strength. Most have a lifespan of 15 years, with hardness, color and gloss retention (sun fading) and manual mixing towards consistent quality being the most common problems in keeping the desired object at an aesthetically pleasing level.

Quality Comparison of paints technologies

In case written in bold font it means existing shortcomings in quality.

Characteristics	Acrylic Latex walls ceilings	Acrylic walls floors	Epoxy floors	Polyurethane waterproofing	CERAMIC® all surfaces
Primer	Yes	Yes	Yes	Yes	No
Adhesion Strength	Poor	Poor	Poor	Poor	Excellent
Cross Cut Test	Poor	Poor	Good	Poor	Excellent
Abrasion Resistance	Poor	Poor	Average	Poor	Excellent
UV Radiation Resistance	Average	Average	Poor	Good	Excellent
Artificial Atmospheric Agents	Poor	Poor	Good	Good	Excellent
Colour Retention	Average	Average	Poor	Poor	Excellent
Gloss Retention	Poor	Poor	Poor	Poor	Excellent
Chemical Resistance	Good	Good	Good	Poor	Excellent
Severe Chemical Attack	Poor	Poor	Average	Poor	Excellent
Temperature Resistance	140°F	196°F	350°F	505°F	600°F
Thermal Shock Resistance	Good	Good	Poor	Good	Excellent
Carbon Dioxide Permeability	Poor	Poor	Good	Poor	Excellent
Permeability water vapour	Average	Average	Good	Average	Excellent
Water Absorption Rate	5-15%	1%	2%	3%	0%
Aging at 158°F	Poor	Poor	Good	Average	Excellent
Adhesion Strength Pull-off	Poor	Average	Good	Poor	Excellent
Impact Resistance	Poor	Average	Good	Poor	Excellent
Anti-Graffiti	No	No	No	No	Yes
Anti-Termite (Wood)	No	No	No	No	Yes
Hydrophobic Self Cleaning	No	No	No	No	Yes
Easy to Clean	No	No	No	No	Yes
Total Solar Reflectance (TSR)	60 (white)	60 (white)	60 (white)	60 (white)	88 (white)
Expected Lifetime in Years	<7	<7	<5-15	<5-15	15-30+

Permanent Coating Protection Plan for Industrial Objects



[SIX1] 2K Primer

(Steel / aluminum surfaces)
Primer must pass
ASTM D3359
adhesion test 5.

2K/1K Egg-shell



[SI13-SI15] Paint White

25/20 Years+ Protection

2K Transparent



[SI11-SI12] Topcoat

30 Year+ Protection

2K Strongest



[SI21-SI22] Paint White

25 Year+ Protection

2K Textured



[SI31] Topcoat Transparent

30 Years+ Protection

If you want to color a transparent topcoat in a custom color, the tinting machine automatically chooses between SI11 Transparent or SI21 Medium White

This ensures the highest quality of the final mixture in combination with the most economical use of color pigments.



APPLY
VIDEO
SCAN
QR CODE



SI11/SI12 2-Component (2K)

Topcoat Transparent
for glossy and matt surfaces

Product ID	: SI112000 67 oz / 4.2 lbs SI122000 67 oz / 4.4 lbs
Consumption	: 3 layers 0.06 lbs/ft ² - 0.96 oz/ ft ² = 3 mil / 70 ft ²
Reachable area	: 2 layers 0.04 lbs/ft ² - 0.64 oz/ ft ² = 2 mil /140 ft ² : 1 layer 0.02 lbs/ft ² - 0.32 oz/ ft ² = 1 mil / 210ft ²
Hardness	: H9
Used for	: Gelcoat, fiberglass, steel, aluminum, plastics, wood, radiator tubes, walls, floors practically any surface.
Application field	: Buildings, factories, offshore structures, bridges, dll.

SI11/SI12 is an incredibly strong 2-component paint system which forms a durable matrix of molecular bonds (transformation to ceramic) resulting in permanent protection of the surface.

Three simple steps: Clean, Dry, and Apply.

- Easily repels water, dirt, dust, and pollutants.
- This coating is permanent hydrophobic.
- Restores damaged finishes and reduces cleaning intervals.
- Resistant to all kinds of chemicals and UV radiation.
- Superior anti-pollution and anti-corrosion properties.
- This coating can withstand temperatures of 300°C.

Expected Life Duration up to 30 years+



How to use: Page 29

- Easy to apply**
- Repaintable**
- Cut maintenance costs**
- Anti-water spot**
- Anti-corrosion**
- Permanent hydrophobic**
- Self-cleaning stays cleaner longer**
- Impact Resistance 1kg / 2lbs**
- Thermal Shock-Resistant**
- Protects your investment**



SI21/SI22 2-Component (2K)

The Strongest White Paint
for glossy and matt surfaces

Product ID	: SI212000 67 oz / 5.3 lbs SI222000 67 oz / 5.5 lbs
Consumption	: 3 layers 0.044 lbs/ft ² - 0.56 oz/ ft ² = 3 mil /120 ft ²
Reachable area	: 2 layers 0.030 lbs/ft ² - 0.37 oz/ ft ² = 2 mil /160 ft ² : 1 layer 0.014 lbs/ft ² - 0.19 oz/ ft ² = 1 mil /240 ft ²
Hardness	: H8
Used for	: Gelcoat, fiberglass, steel, aluminum, plastics, wood, radiator tubes, walls, floors practically any surface.
Application field	: Buildings, factories, offshore structures, bridges, dll.

SI21/SI22 is a medium white 2-component paint that binds molecules and (conversion to ceramic) provides permanent protection on applied surfaces.

Three simple steps: Clean, Dry, and Apply.

- Easily repels water, dirt, dust, and pollutants.
- This coating does not absorb any water
- Resistant to all kinds of chemicals and UV radiation.
- This coating can withstand temperatures of 300°C

Expected Life Duration up to 25 year+



How to use: Page 29

- Easy to apply**
- Repaintable**
- Cut maintenance costs**
- Anti-water spot**
- Anti-corrosion**
- Permanent hydrophobic**
- Self-cleaning stays cleaner longer**
- Impact Resistance 1kg / 2lbs**
- Thermal Shock-Resistant**
- Protects your investment**



TEST
REPORT
SCAN QR
CODE



SI31 2-Component (2K)

Textured Transparent Semi Gloss
antislip - high impact resistant



How to use: Page 29

Product ID	: SI312000 67 oz / 4.6 lbs
Consumption	: 3 layers 0.050 lbs/ft ² - 0.76 oz/ ft ² = 3 mil / 90ft ²
Reachable area	: 2 layers 0.033 lbs/ft ² - 0.51 oz/ ft ² = 2 mil / 180ft ²
	: 1 layer 0.017 lbs/ft ² - 0.25 oz/ ft ² = 1 mil / 270ft ²
Hardness	: H9
Used on	: Gelcoat, fiberglass, steel, aluminium, plastics, wood, virtually any surface.
Application area	: Buildings, factories, offshore structures, bridges, dll.

SI31 is a clear solvent-based ceramic coating, linked with a ceramic activator, available in semi-gloss and includes sprayable nano particles. Known for its exceptional durability, this coating easily applies to any organic surface without needing a primer. Its textured design makes it perfect for anti-slip needs.

- Easily repels water, dirt, dust, and pollutants.
- This coating has an outstanding hydrophobic effect.
- Resistant to all kinds of chemicals and UV radiation.
- This coating can withstand temperatures of 600°F.
- Zero absorption, waterproof, insulation and heat rejecting

Expected Life Duration up to 30 years+




SI13 (2K) / SI15 (1K)

The Coolest White Paint
for egg-shell surfaces



How to use: Page 29



Product ID	: SI132000 67 oz / 7.3 lbs SI152000 67 oz / 6.6 lbs
Consumption	: 2 layers 0.050 lbs/ft ² - 0.48 oz/ ft ² = 3.5 mil / 140 ft ²
Reachable area	: 1 layers 0.025 lbs/ft ² - 0.24 oz/ ft ² = 1.8 mil / 280 ft ²
Hardness	: H7
Used for	: Concrete, steel, wood, acrylic, gypsum
Application field	: Buildings, factories, offshore structures, bridges, dll.

SI13/SI15 is an incredibly strong 2-component eggshell paint system which forms a durable matrix of molecular bonds (transformation to ceramic) resulting in permanent protection of the surface.

Three simple steps: Clean, Dry, and Apply.

- Easily repels water, dirt, dust, and pollutants.
- This coating does not absorb any water
- Resistant to all kinds of chemicals and UV radiation.
- This coating can withstand temperatures of 300°C

Expected Life Duration up to 25 year+ or 20 year+



Color mixing has never been so easy!!!

X- SMART is the modular version of the acclaimed dispenser series, extremely cost-effective and easy to operate, with a low maintenance

This color mixer has a robust and tubeless design, built with a patented pump technology (to reduce waste) and identical features, making it a highly advanced dispenser, ideally suited to reduced capacity.



X-SMART
Stabilizer plates

16 High Grade Coloring chemicals



Titanium White
Masstone Tint 844-0061 1.05 gal



Quinacridone Red
Masstone Tint 844-0451 32 oz



Scarlet Red
Masstone Tint 844-0526 32 oz



Lead Free Orange
Masstone Tint 844-0982 32 oz



Trans Red Oxide
Masstone Tint 844-1054 32 oz



Red Oxide
Masstone Tint 844-1063 32 oz



Burnt Umber
Masstone Tint 844-1352 32 oz



Trans Yellow Oxide
Masstone Tint 844-1852 32 oz



Yellow Oxide
Masstone Tint 844-1863 32 oz



Lead Free Med Yellow
Masstone Tint 844-2555 32 oz



Yellow
Masstone Tint 844-2826 32 oz



Organic Yellow
Masstone Tint 844-2852 32 oz



PHTHALO Green
Masstone Tint 844-5558 32 oz



Quinacridone Violet
Masstone Tint 844-9451 32 oz



Lamp Black
Masstone Tint 844-9955 32 oz



PHTHALO BLUE
Masstone Tint 844-7262 32 oz

Color card

Residential		
SI13 White Egg-Shell (Flat Finish) 15/25 (20/60°)	SI41 Textured White Semi Gloss 41/69 (20/60°)	
SI15 White Egg Shell (Flat Finish) 18/28 (20/60°)	SI42 Textured White Matte 11/21 (20/60°)	
SI21 White Gloss 49/77 (20/60°)		
SI22 White Satin 33/59 (20/60°)		
Original	RAL 9018	RAL 3015
Cool white	Papyrus white	Light pink
RAL 9001	RAL 9022	RAL 5007
Cream white	Pearl light grey	Pastel blue
RAL 9002	RAL 9023	RAL 4009
Grey white	Pearl dark grey	Pastel violet
RAL 9003	RAL 1000	RAL 6027
Signal white	Green beige	Light green
RAL 9004	RAL 1001	RAL 7000
Signal black	Beige	Squirrel grey
RAL 9005	RAL 1002	RAL 1036
Jet black	Sand yellow	Pearl gold
RAL 9006	RAL 1011	RAL 8029
White aluminium	Brownbeige	Pearl copper
RAL 9007	RAL 1013	RAL 4012
Grey aluminium	Pearl white	Pearl blackberry
RAL 9010	RAL 1014	RAL 5025
Pure white	Ivory	Pearl gentian blue
RAL 9011	RAL 1015	RAL 6036
Graphite black	Light ivory	Pearl opal green
RAL 9016	RAL 9017	MAHOGANY braun

Wood

SI11 Transparent Gloss 51/78 (20/60°)
SI12 Transparent Matte 11/21 (20/60°)



SI11 Transparent



SI11 Light



SI11 Nut



SI11 Colonial

Industrial

SI11 Transparent Gloss 51/78 (20/60°)
SI21 White Gloss 49/77 (20/60°)
SI22 White Satin 33/59 (20/60°)



Transparent



Luminous yellow



Traffic red



Jet black



Golden yellow [Cat]



Leaf green [J.D Deere]



Light grey



Dark grey



Silver grey



Signal brown



Pale brown

Other colors need minimal 220 lbs

Marine

SI12 Transparent Matte 11/21 (20/60°)
SI1 Textured White Semi Gloss 41/69 (20/60°)
SI33 Textured Black Semi Gloss 41/69 (20/60°)
SI42 Textured White Matte 11/21 (20/60°)

Original



Cool white



RAL 9010



RAL 9001



RAL 5023



Jet black



Traffic yellow



Silver gray



Light grey



Light grey



Light grey



Light grey



Light grey



Light grey



Light grey



Light grey

Military

Original



RAL 3000



RAL 3004



RAL 7031



RAL 6031



RAL 6451



RAL 7015



RAL 5008



RAL 7004



Signal Grey

Antifouling

Original



RAL 3000



RAL 3004



RAL 7031



RAL 6031



RAL 6451



RAL 7015



RAL 5008



RAL 7004



Signal Grey

Antifouling

SI14 Color 31/41 (20/60°)



Transparent



Jet Black



Signal Red



Ultra marine blue



Signal Grey



SIX1

2-Component (2K)

Primer Epoxy Polyamide

heavy duty - anti-corrosion

Product ID : SIX11250-WH/GR 42 oz / 3.2 lbs SIX15000-WH/GR 1.32 gal / 12.8 lbs
Consumption : 2 layers +/- 0.53 lbs/ft² - 0.7 oz/ft² 80 micron = 50 ft²
Reachable area : 1 layer +/- 0.26 lbs/ft² - 0.4 oz/ft² 40 micron = 100 ft²
Hardness : H5
Colors : White, Grey or RAL (RAL Minimum Order 250 pcs 1.32 gal)
Used on : Concrete, Steel, Aluminium, Fiberglass and other organic surfaces
Application area : Buildings, marine, airports, offshore structures, bridges



-  **Fast Repaintable**
-  **Excellent adhesion**

SIX1 is a solvent based epoxy polyamide primer. This primer is used for corrosion protection on concrete, stainless, galvanized, carbon and alloy steel, aluminum in corrosive conditions and has excellent adhesion to all organic substrates and to all of our ceramic topcoats. The primer can be applied at a relative humidity of 40-80% and can be painted over within 8 hours 85°F, 1 hours 140°F.

SIX2

2-Component (2K)

Primer Surfacer Acrylic Alkyd

smooth - surface modifier

Product ID : SIX21250-WH/GR 42 oz / 3.2 lbs SIX25000-WH/GR 1.32 gal / 12.8 lbs
Consumption : 2 layers +/- 0.44 lbs/ft² - 0.7oz/ft² 60 micron = 60ft²
Reachable area : 1 layer +/- 0.22 lbs/ft² - 0.4oz/ft² 30 micron = 120ft²
Hardness : H3
Colors : White or Grey
Used on : Steel, aluminium, wood, fiberglass, and old paint systems.
Application area : Buildings, marine, airports, bridges



-  **Fast Repaintable**
-  **Excellent adhesion**
-  **VOC Free**

SIX2 High-quality 2K surfacer (two-component basecoat) for auto-refinish, marine, and industrial coating applications where a smooth surface is required. The primer has excellent adhesion to all organic substrates and to all of our ceramic topcoats. The primer can be applied at a relative humidity of 30-80% and can be painted over within 4 hours 85°F, 1 hours 140°F.



Heavy Duty Primer - Smooth Surfacer



SIX3


2-Component (2K)

Primer PU Wood Filler

surface modifier - absorbtion reducer



Product ID	: SIX31500 51 oz / 3.3 lbs
Consumption	: 2 layers +/- 0.40 lbs/ft ² - 0.6 oz/ft ² 60 micron = 80ft ²
Reachable area	: 1 layer +/- 0.20 lbs/ft ² - 0.3 oz/ft ² 30 micron = 120ft ²
Hardness	: H4
Used on	: Steel, Aluminium and other organic surfaces
Application area	: Buildings, marine, airports, offshore structures, bridges



SIX3 is a solvent borne transparent wood filler. This primer is used as surface modification for, wood or natural stone to reduce capillary absorption and has an excellent adhesion to all organic substrates and towards one of our ceramic top coats. The primer can be applied at a relative humidity of 40-80%.



SIX4

1-Component (1K)

Primer Acrylic Waterbased

all surfaces modifier



Product ID	: SIX41000-WH/GR 32 oz / 2.65 lbs SIX44000-WH/GR 1 gal / 10.6 lbs
Consumption	: 2 layers +/- 0.53 lbs/ft ² - 0.7 oz/ft ² 80 micron = 50 ft ²
Reachable area	: 1 layer +/- 0.26 lbs/ft ² - 0.4 oz/ft ² 40 micron = 100 ft ²
Hardness	: H3
Colors	: White, Grey or RAL (RAL Minimum Order 250 pcs 1gal)
Used on	: Concrete, wood, drywalls and old waterbased paints
Application area	: Buildings, walls and ceilings indoor or outdoor



SIX4 Acrylic Water-Based Primer is a premium, all-purpose primer-sealer with excellent adhesion, stain-blocking, and hiding power. Ideal for both interior and exterior surfaces, it bonds to glossy surfaces without sanding, effectively blocks stains, and provides a smooth foundation for any solvent-based or water-based topcoat.



SIX5

2-Component (2K)

Putty Polyester

ultra smooth - sandable

Product ID : SIX51000-WH/GR 2.2 lbs

Colors : White, Grey

Used on : Metal, wood, fiberglass, concrete, plastics

Application area : Transportation.

SIX5 is a High quality 2 (two) component Epoxy base putty for auto-refinish, marine and industrial coating applications.



Fast Repaintable



Excellent adhesion



SOLV

Thinner solvent

for all types of our ceramic paint & coating

Product ID : SOLV0400 14 oz / 0.8 lbs SOLV2000 64 oz / 3.9 lbs SOLV5000 1.32 gal / 9.7 lbs



All our paints and coatings are ready to use, for certain spray applications, especially dark colors who require more than average color pigments, it may be necessary to use a little thinner solvent to achieve optimum flowability.

RETA/ACCL

Retarder
Accelerator


slow down flash time or speed up curing



Product ID : RETA0400 14 oz / 0.85 lbs ACCL0200 7 oz / 0.4 lbs

If your application needs a longer flash time (for example, in hot temperatures) to build up the layer with a second or third coat, you can add the RETA Retarder. If you want to speed up the curing process, you can add the ACCL Accelerator. It can reduce curing time by 30–70% compared to uncatalyzed systems, and full hardness can develop 1.5–2x faster.

Scan QR Code for TDS and SDS



Video Application & (Test) Results



SGS TEST
REPORTS
SCAN
QR-CODE



TECHNICAL
VIDEO
SCAN
QR-CODE



TEST REPORT
EN 1504-2
SCAN
QR-CODE

TSUG

How to use our UVA Coating System:

These products can be stored for up to 24 months (*in a dry, temperature-stable dark environment*)

Processing Temperature:

Ambient temperature: 41-86°F
Avoid direct sunlight, Rain and /or high humidity.

IMPORTANT:

Before you use a NANO-CERAMIC product, please make sure you wear suitable protection gear. We always recommend using a paint suit, respirator mask and latex or nitrile gloves.

Outfit/Applicators:



Fresh Air Respirator



Paint Suit



Nitrile gloves

Instructions for use:

Protect or Renew; Marble, Granite, Varnished wood, HPL, PVC or Vinyl laminate and Melamine. Creates an easy-to-clean, anti-scratch surface that is resistant to UV Discoloration, HF (Hydrofluoric Acid), Hydro-chloric Acid, and Citric Acid.

Wipe Application; 1. Clean the surface 2. Sterilize the surface 3. Apply via the cotton pad an even layer 4. Let it cure.

Spray Application; Use an HVLP (High Volume Low Pressure) spray gun with 60-80% transfer efficiency. Fit the spray gun with a 1.0-1.3 mm fluid tip. Set air pressure to 20-30 psi.

Preparation Steps:

1. Stir the coating thoroughly for 30 seconds before use.
2. Prior to application, strain the mixed coating through a suitable paint filter (e.g., 190-250 µm) to ensure a clean, defect-free spray.
3. Wash and decontaminate the surface.
4. Wet sand / scuff using 1500-2000 grit sandpaper.
5. Mask off any parts not to be coated.
6. Ensure environmental conditions are below 65% humidity.
7. Perform a final clean using 100% acetone.
8. Wipe with a tack cloth to remove any dust or lint.

Application Procedure:

1. Spray a light, even coat. Allow a 5-minute flash-off time, or until outgassing stops.
2. Apply a second coat. Allow to flash off for at least 15 minutes, or until outgassing stops.
3. Unmask carefully before the coating fully cures.

Curing:

Tough Dry 5min, Hard Dry 2 Hours, 85% Cured 12 Hours, 100% Cured 5 Days. Refer to the TDS/SDS for more information.



How to use our Permanent Coating System:

These products can be stored for up to 24 months (*in a dry, temperature-stable dark environment*)

Processing Temperature:

Ambient temperature: 41-86°F
Avoid direct sunlight, Rain and /or high humidity.

IMPORTANT:

Before you use a NANO-CERAMIC product, please make sure you wear suitable protection gear. We always recommend using a paint suit, respirator mask and latex or nitrile gloves.

Outfit/Applicators:



Fresh Air Respirator



Paint Suit



Nitrile gloves

Application information

The SI11/SI12/SI21/SI22/SI31/SI33 coatings can be applied directly or indirectly on all surfaces (porous and non-porous) such as concrete, steel, wood, acrylic, gypsum, painted or unpainted surfaces, indoors, or outdoors. The surface underneath will be superbly protected against erosion and corrosion and will stay cleaner longer. Cleaning becomes quicker, easier, and less expensive, as special cleaning agents are unnecessary.

Preparation


Make sure the surface is free from any contamination and dirt. A zinc rich primer can be used in case of problems with the substrate. **Warning the surface must be completely dry before application and must stay dry for 6 hours after application!**

The 2-Component Permanent Coating System

Mix the can SI11B-SI12B-SI21B-SI22B-SI31B-SI33B with the can of SI11A-SI12A-SI21A-SI22A-SI31A-SI33A by pouring can B into can A, or measure exactly by net weight in a ratio of 7:3 and mix very well, or measure exactly by net weight in a ratio of 9:1 and mix thoroughly with a power agitator.

The 2-Component Permanent Coating System

Mix the can SI11B-SI21B-SI32B-SI33B with the can of SI11A-SI21A-SI32A-SI33A by pouring can B into can A, or measure exactly by net weight in a ratio of 9:1 and mix very well. Mix the can of SI21B with the can of SI21A by pouring can B into can A, or measure exactly by net weight in a ratio of 9:1 and mix thoroughly with a power agitator. Carefully pour the mixed contents into a professional paint sprayer, and spray in thin layers until the surface reaches your desired thickness. Let the surface dry for 24 hours. It is touch-dry in 1 hours, after 4 hours, 85% cured, and the remaining 15% (transformation into ceramics) is fully cured after



NANO-CERAMIC®

WWW.NANO-CERAMIC.COM INDUSTRIAL PROTECTIVE COATINGS



The Leader in Durability

Did you know?

That our coatings are made of pure silica sand, which is the most common element on Earth?

Dealer